



LOS MEJORES EQUIPOS EN SEGURIDAD

---

## BULLET CAMERA



REFERENCIA

S-D B 36IRJ1

1/3 SONY SUPER HAD CCD 420TVL (3142+633), 0Lux with  
3.6mm Lens 36 LEDS  $\phi$  5 IR leds 30M IR Distance DC12V, dual  
glass with bracket silver color



REFERENCIA

S-D B 36IRJ2

1/4 SHARP CCD 420TVL, 0Lux/F1.2 with 3.6mm Lens, 36 LEDS  
 $\phi$  5 IR leds 30M IR Distance with bracket silver color



REFERENCIA

S-D B 36IRJ3

1/3 SONY SUPER HAD CCD 470TVL (3142+633), 0Lux with  
3.6mm Lens 36 LEDS  $\phi$  5 IR leds 30M IR Distance DC12V, dual glass with bracket  
silver color





LOS MEJORES EQUIPOS EN SEGURIDAD

---

## BULLET CAMERA

**REFERENCIA**  
**SD B36IRS**



1/4" Sharp Low Illumination CCD, 420TV Lines Waterproof IR camera  
3.6mm board lens|36pcs Ø5mm IR LEDs IR distance: 30m 0lux with  
IR onwaterproof:IP66142(W)x83(D)x83(H)mm0.5kg

---

**REFERENCIA SB 36IRJ8**  
**Color 1/3 700 TV Lines**  
**Low**



### **Illumination**

**IR LED:  $\phi$  5X72 LEDS IR LED**  
**working distance: 60M**

High resolution: 700 TV Lines  
optional

Built-in bracket, 3-Axis direction  
bracket

**Lens: 4-9mm Manual Zoom Lens**

**New Housing Design, IP66 waterproof**

Dimension: 240(W)x186(H)x100(D)mm Weight:1.5Kg Color 1/3" SONY 700TVL,  
Low Illumination, DWDR, OSD, DNR [Sony 672/673 + EOS801](#)





LOS MEJORES EQUIPOS EN SEGURIDAD

---

## DOME CAMERA

---



**REFERENCIA S-D D24IR Color 1/4" SHARP,420 TV Lines  
Low Illumination Plastic IR Dome Camera**

**IR LED:  $\phi$  5X24 LEDS IR LED working distance:  
20M**

SONY/Sharp Color CCD  
High resolution: 420TV Lines optional



3-Axis bracket built-in

Lens: Board Lens 3.6mm/F2.0

Dimension:  $\phi$  94 x 69(H) mm Weight:250g

---



**REFERENCIA S-D D24IRV Color 1/4" SHARP, 420 TV Lines  
Low Illumination Vandalproof IR Dome Camera**

**IR LED:  $\phi$  5X24 LEDS IR LED working distance: 20M**

SONY/Sharp Color CCD  
High resolution:/420TV Lines  
3-Axis bracket built-in  
Lens: Board Lens 3.6mm/F2.0

Dimension:  $\phi$  94 x 69(H) mm Weight:400g



[Antivandalica](#)

---



**REFERENCIA  
S-D D 24IRJ1**

1/3 SONY SUPER HAD CCD **500TVL** (3142+633),0Lux/F1.2  
with **3.6mm Lens**,24pcs  $\phi$  5 IR leds **25M IR Distance**

DC 12V Metal case, silver color

[Antivandalica](#)

---



## LOS MEJORES EQUIPOS EN SEGURIDAD

---

### REFERENCIA S-D D SD 36IRJ3



Vandalproof IR Dome Camera  
Sony super had 480 tvl IR LED:  $\phi$  5X36PCS IR range: 30M  
**VARIFOCAL LENSE 2.8-12mm Manual Zoom Lens**  
**(2M Pixels)**  
Size:  $\phi$  131 x 93(H) mm

Weight: 800g

[Antivandalica](#)

---

### REFERENCIA S-D SD 36IRJ2

1/3 SONY SUPER HADII CCD **700 TVL** (4127+673) Sony Effio-E 0Lux/F1.2 with **2.8-12mm Lens**, 36pcs  $\phi$  5 IR leds **30M IR Distance** DC 12V Metal case



OSD Menu Controller



LOS MEJORES EQUIPOS EN SEGURIDAD

---

## SPY CAMERA



**REFERENCIA**  
**S-D P 36IRJ1**



1/3 SONY SUPER HAD CCD **480TVL** (3142+633) 0.5Lux/F1.2  
with **3.6mm lens** DC 12V

**REFERENCIA**  
**S-D P SJ2**



1/3 SONY SUPER HAD CCD **480TVL** (3142+633) 0.5Lux/F1.2 with **3.6mm lens** DC  
12V



LOS MEJORES EQUIPOS EN SEGURIDAD

---

**LINEA SUPER ECONOMICA DVR**

**S-DJ DVR 04**



4CH Standalone DVR, with VGA port, support 3G device.H264

---

**S-DJ DVR 08**



8CH Standalone DVR,with VGA port, support 3G device.H264

---

**S-DJ DVR 16**



16CH Standalone DVR,with VGA port, support 3G device.H264

---



LOS MEJORES EQUIPOS EN SEGURIDAD

---

## S-DJ DVR 16

DVR 16 L HL



### DVR ALTA DEFINICION



Video Input/output: BNC 16CH In / 2CH Out, VGA  
1CH Out,

### HDMI 1CH Out

Audio Input/output: RCA 16CH In/ 1CH Out  
Alarm Input/output: Alarm 16CH In/ 2CH Out  
Compression Method: H.264

Real time recording support:

CIF:352x240 with 480 Fps (NTSC); 352x288 with 400 Fps (PAL)

D1:720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL)

Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL );

Playback resolution: CIF x 16 / D1 x 1

Hexaplex operation simultaneously: Preview, recording,  
playback, and network live, backup, playback

1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS,

Support Internet Explorer and special client software

Remote Control, PTZ, RS485x2, 2xUSB, 1xIR Controller

2 SATA Hard Disk interface

Backup: USB2.0 and Network **D1\*4CH,RS485, PTZ, Alarm, Network**

Support remote view by Mobilephone **2 SATA HD,HDMI,VGA, USB Backup, USB Mouse**

Dimensions (LxWxH): 405mmx325mmx65mm, weight: 6kg





LOS MEJORES EQUIPOS EN SEGURIDAD

---

## SPEED DOME IR PTZ

REFERENCIA  
S-D- IR SPEED DOME 18X SONY



Sony brand Zoom module, low lux Color to black ,ICR 530TVL, 18X Optical Zoom 12X digital Zoom, **with WDR**.NTSC system

---

REFERENCIA  
S-D- IR SPEED DOME 36X SONY



Sony brand Zoom module, low lux Color to black ,ICR 530TVL, 36X Optical Zoom 12X digital Zoom, **with WDR**.NTSC system

---

REFERENCIA  
S-D- IR SPEED DOME 26X LG



LG brand Zoom module, low lux Color to black ,ICR 530TVL, 26X Optical Zoom 12X digital Zoom. NTSC system **LG brand Zoom module Color to black, ICR 540TVL 26X optical zoom 12X digital zoom.**





LOS MEJORES EQUIPOS EN SEGURIDAD

---

## SPEED DOME PTZ



---

Pan 360° continuously, tilt 90°,180° auto flip,pan speed 0-280 degree  
tilt speed 0-120 degree

2. Support Display the level&vertical position and Zooming times
3. Support alarm linkage,8 ways alarm in 2 ways alarm out
4. 128 preset positions,4 patterns scan,each patter recording time is above 15 minutes
5. intelligent focus,speed auto matching technology
6. 8 areas privacy protection
7. Built in 6000V lighting protection, Surge proof design
8. Working temperature:-40°C-65°C
9. Power supply:DC15V 2A or AC24V 2A

**LG brand Zoom module Color to black, ICR 540TVL 26X optical zoom 12X digital zoom**

---

## MINI PTZ



---

**1/4" Super HAD Color CCD, ICR, 10X (f=3.8~38mm), Color 500TVL, Black 570TVL**

★Vandal proof Mini Speed Dome Camera

★Pan range: 0°~360° Continue

★Tilt range: 0°~90° Flip

- ★Pan Speed: Max 50°/sec
- ★Preset: 16
- ★Weatherproof Outdoor IP66
- ★RS485, Pelco D/P supported
- ★10X (f=3.8~38mm) Size: Ø121x177m



LOS MEJORES EQUIPOS EN SEGURIDAD

---

## MINI CONTROLLER PTZ

### REFERENCIA S-D PTZ 3D



3D PTZ Controller



- ★Set or call the set points and cruise tracks
- ★Manually or automatically control
- ★RS-485/RS-232 communication
- ★Baud rate: 2400-19200Bps
- ★Communication distance: Max.1200m
- ★Size: 95(H)X205(L)X205(W) mm
- ★Weight: 2Kg

3D PTZ Controller





LOS MEJORES EQUIPOS EN SEGURIDAD

---

## ACCESORIES CCTV

### REFERENCIA S-D VBK2



#### **1CH Passive video balun**

Transmission distance about 600M(W/B  
Video): about 400M(Color Video), "Press-fit" terminal Block. Wire  
type: One Unshielded Twisted Pair 24-16AWG(0.5-1.31mm) Per video  
signal Loop Resistance 52 ohms per 1,000 ft(18 ohms per 100m)



#### **1CH Active Transmitter**

Power in: 12-24V AC/DC, Video in: BNC (female)  
Transmission distance: Max. **1800m(Color)** or 2400m (B/W)  
Video format: NTSC/PAL/CCIR/SECAM analog real-time signal  
Frequency Range: DC--6MHz; Common Mode Rejection: 60db  
Twisted Pair Connector: Two Pin Connector  
Surge-suppression: 6KV 10\*700us IEC61000-4-5  
Dimensions with BNC: 81\*82\*29mm





LOS MEJORES EQUIPOS EN SEGURIDAD

## ACCESORIES CCTV

### POWER SUPPLY



#### REFERENCIA S-D PWSK1



DC12V,1A. US Standard.

#### REFERENCIA S-D PWSK1.5

DC12V, 1.5A US Standard.



Recibimos todas las tarjetas de crédito

